



# PATMOS C 3M1


Standard



Piedi verniciati tub.  
Prepainted tube legs



Piedi ciechi verniciati  
Prepainted blind legs



Temperatura d' esercizio Running temperature Temperature de fonctionn. Betriebstemperatur Temperatura de ejercicio	0°C/+2°C
Condizioni ambientali Ambient conditions Condition ambient Umweltbedingungen Condiciones ambientales	+25°C - 60% U.R.


Lunghezza / Length / Longeur / Lange / Largo	mm	937	1250	1562	1875	2500	3125	3750
Spessore spalla / Thickness of end / Espaisseur joue / Seitenteil dicke / Espesor del lateral	mm	40	40	40	40	40	40	40
Volume lordo / Gross volume / Volume brut / Bruttoinhalt / Volumen bruto	dm <sup>3</sup>	165	220	275	330	440	550	660
TDA - Total display area	m <sup>2</sup>	0,98	1,31	1,64	1,97	2,62	3,28	3,93
Rumorosità / Sound level / Bruit / Geräusentwicklung / Rumorosidad	dBA	<52						
Quadro elettrico / Electric control panel / Tableau électrique / Steuerung / Tablero electrónico	mod.	--	--	--	--	--	--	--
Orificio / Orifice / Orifice / Düse / Orificio	nr.	TES2 or.00	TES2 or.00	TES2 or.00	TES2 or.00	TES2 or.01	TES2 or.01	TES2 or.01
Potenza frigo alla temperatura di evaporazione Reale / Refrigeration duty at real evaporating temperature / Puissance frigorifique a la température d'évaporation réelle / Kälteleistung mit tatsächlicher verdampfungstemperatur / Potencia frigorífica a la	-8 C° watt	280	380	470	570	760	950	1140
Potenza frigo alla temperatura di evaporazione Nominale / Refrigeration duty at nominal evaporating temperature / Puissance frigorifique avec température nominale / Kälteleistung mit nominaler temperatur / Potencia frigorífica a temperatura evaporacion no	-10 C° watt	260	350	440	530	700	880	1060
Potenza elettrica nominale / Rating power / Puissance absorbée / Leistungsaufnahme / Potencia absorbida	watt	74	93	130	149	204	242	297
	A	0,32	0,40	0,56	0,65	0,89	1,05	1,29
Potenza in sbrinamento / Defrosting power / Puissance pour le dégivrage / Abtaugleistungsaufnahme / Potencia descongelación	watt	449	593	755	899	1204	1492	1797
Consumo elettrico giornaliero indicativo / Daily electrical consumption / Consommation électrique quotidienne indicative / Ungefährer stormtagesverbrauch / Consumo elettrico diario	KWh/24	2,3	3,0	4,1	4,7	6,4	7,7	9,4
Ventilatori evaporatore / Evaporator fans / Ventilateurs evaporateur / Verdampfer ventilator / Ventiladores evaporador	nr. x watt	1x18	1x18	2x18	2x18	3x18	3x18	4x18
Illuminazione standard/ Lighting standards / Normes sur l'éclairage / Standard-Beleuchtung / Estándar de la Iluminación	nr. x watt	np	np	np	np	np	np	np
Resistenza anticondensa / Antimist heater / Resistance anti-buues / Antibeschlagheizung / Resistencia anti condensación	watt	56	75	94	113	150	188	225
Resistenza sbrinamento / Defrost heater / Resistance degivrage / Abtaheizung / Resistencia de desescarche	nr. x watt	1x375	1x500	1x625	1x750	1x1000	1x1250	1x1500
Nr. of defrost in the 24h	nr. x 24h	3	3	3	3	3	3	3

## Opzioni / Option / Les options / Optionen / Opciones


Ill. frontale LED \ LED front lighting \ Eclairage frontal LED \ Front LED beleuchtung	nr. x watt	1x10	1x13	1x17	1x18	2x13	2x17	2x18
--	------------	------	------	------	------	------	------	------

# PATMOS C 3M2


Standard



Piedi verniciati tub.  
Prepainted tube legs



Piedi ciechi verniciati  
Prepainted blind legs



Temperatura d' esercizio Running temperature Temperature de fonctionn. Betriebstemperatur Temperatura de ejercicio	+3°C/+5°C
Condizioni ambientali Ambient conditions Condition ambient Umweltbedingungen Condiciones ambientales	+25°C - 60% U.R.

Lunghezza / Length / Longeur / Lange / Largo	mm	937	1250	1562	1875	2500	3125	3750
Spessore spalla / Thickness of end / Espaisseur joue / Seitenteil dicke / Espesor del lateral	mm	40	40	40	40	40	40	40
Volume lordo / Gross volume / Volume brut / Bruttoinhalt / Volumen bruto	dm <sup>3</sup>	165	220	275	330	440	550	660
TDA - Total display area	m <sup>2</sup>	0,98	1,31	1,64	1,97	2,62	3,28	3,93
Rumorosità / Sound level / Bruit / Geräusentwicklung / Rumorosidad	dBA	<52						
Quadro elettrico / Electric control panel / Tableau électrique / Steuerung / Tablero electrónico	mod.	--	--	--	--	--	--	--
Orificio / Orifice / Orifice / Düse / Orificio	nr.	TES2 or.00	TES2 or.00	TES2 or.00	TES2 or.00	TES2 or.01	TES2 or.01	TES2 or.01
Potenza frigo alla temperatura di evaporazione Reale / Refrigeration duty at real evaporating temperature / Puissance frigorifique a la température d'évaporation réelle / Kälteleistung mit tatsächlicher verdampfungstemperatur / Potencia frigorífica a la	-6 C° watt	250	330	420	500	670	840	1000
Potenza frigo alla temperatura di evaporazione Nominale / Refrigeration duty at nominal evaporating temperature / Puissance frigorifique avec température nominale / Kälteleistung mit nominaler temperatur / Potencia frigorífica a temperatura evaporacion no	-10 C° watt	220	290	360	430	580	720	870
Potenza elettrica nominale / Rating power / Puissance absorbée / Leistungsaufnahme / Potencia absorbida	watt	74	93	130	149	204	242	297
	A	0,32	0,40	0,56	0,65	0,89	1,05	1,29
Potenza in sbrinamento / Defrosting power / Puissance pour le dégivrage / Abtaugleistungsaufnahme / Potencia descongelación	watt	74	93	130	149	204	242	297
Consumo elettrico giornaliero indicativo / Daily electrical consumption / Consommation électrique quotidienne indicative / Ungefährer stormtagesverbrauch / Consumo elettrico diario	KWh/24	1,8	2,2	3,1	3,6	4,9	5,8	7,1
Ventilatori evaporatore / Evaporator fans / Ventilateurs evaporateur / Verdampfer ventilator / Ventiladores evaporador	nr. x watt	1x18	1x18	2x18	2x18	3x18	3x18	4x18
Illuminazione standard / Lighting standards / Normes sur l'éclairage / Standard-Beleuchtung / Estándar de la Iluminación	nr. x watt	np	np	np	np	np	np	np
Resistenza anticondensa / Antimist heater / Resistance anti-buues / Antibeschlagheizung / Resistencia anti condensación	watt	56	75	94	113	150	188	225
Resistenza sbrinamento / Defrost heater / Resistance degivrage / Abtauheizung / Resistencia de desescarche	nr. x watt	np	np	np	np	np	np	np
Nr. of defrost in the 24h	nr. x 24h	3	3	3	3	3	3	3

## Opzioni / Option / Les options / Optionen / Opciones

Ill. frontale LED \ LED front lighting \ Eclairage frontal LED \ Front LED beleuchtung	nr. x watt	1x10	1x13	1x17	1x18	2x13	2x17	2x18
--	------------	------	------	------	------	------	------	------